



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

## **STL Prime® 27" TIR MaxGen™ (U.S. Patent No. D703,082) Operation Manual and Instructions**

Congratulations, you are the owner of a STL Prime ® Series Light bar! Your bar is equipped with the latest technology and features at the best value found industry wide, GUARANTEED. In addition to that, your purchase comes with the STL 5 Year Warranty against any manufacture defects that may occur with your bar. So please read this document carefully and call Customer Service at 800-757-2581 Monday - Friday 8:30 AM - 4:30 PM central time if you need assistance. We are available and happy to help!

### **Warnings and Notices for Users and Installers**

This document must be delivered to and read by the end user and installer as it serves to provide you with the required information for proper and safe use of your STL product. Before operating this or any STL products the user and installer must read this manual all the way through. You will find important information in this manual that could prevent property damage and/or serious injury to the user and installer.

STL products are intended to alert pedestrians and other operators of the presence of personnel, the operation of emergency vehicles, an emergency site, and any warning needs. This does not ensure that pedestrians or drivers will react, heed, or observe emergency warning signals. Nor does the use of emergency signals grant or ensure you the right of way. It is your responsibility to make sure you can proceed safely before driving against traffic, entering an intersection, responding at a high rate of speed, or walking on or around traffic lanes.

Your STL emergency vehicle devices should be tested daily to insure the device and all its functions are operating correctly. If you experience a malfunction contact STL's Customer Service immediately for troubleshooting options, or a warranty or service claim. You must ensure sure that the projection of the visual and audible signal is not blocked by vehicle components (i.e.: open trunks, visors, compartment doors), vehicles, other obstructions, or people.

This is professional grade equipment and is intended for strict use by authorized personnel only. It is the user's responsibility to understand and obey all laws regarding emergency warning devices. You must know and be familiar with all applicable city, state, and federal laws and regulations prior to the use of emergency vehicle warning devices.



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

SpeedTech Lights, Inc. assumes no liability for any loss resulting from the use of this warning device. Proper installation is vital to the performance of the warning devices and safe operation of the emergency vehicle. Since the operator is under stressful environments the equipment must be properly wired and mounted to ensure effectiveness and safety. Therefore controllers must be properly installed and placed within convenient reach of the operator so eye contact with the roadway is never lost.

The effectiveness of your STL equipment is highly dependent upon correct mounting and wiring. Improper wiring and mounting of the warning device will reduce the output and performance of the equipment. Emergency warning devices frequently require high electrical voltages and/or currents. Properly protect and use caution around live electrical connections. Grounding or shorting of electrical connections can cause high current arcing, which can cause severe personal injury and/or serious vehicle damage, including fire.

Electromagnetic interference can be caused by many electronic devices used in emergency vehicles. To ensure that this doesn't happen to you, lightbars should be mounted a minimum of 12" - 34" from the radio antenna and do not power your equipment from the same circuit or share the same grounding circuit with radio communication equipment. After installation, test all the vehicle's equipment together to ensure everything operates free of interference.

Driver and/or passenger airbags bags (SRS) will impact the way you mount your equipment. Any equipment installed in the deployment area of the airbags will damage or dislodge the airbags and sensors. This will also reduce the effectiveness of the airbags to protect the passengers and therefore these areas must be avoided. Installers must make sure that this equipment along with any parts, hardware, wiring, power supplies, and switch boxes do not interfere with the airbags, SRS wiring, or sensors.

All STL equipment needs to be mounted and installed according to the vehicle manufacture's instructions and securely attached to a part of the vehicle of sufficient strength to withstand the forces applied by the equipment. This device should be permanently mounted within the zones specified by the vehicle manufacturer. This especially applies to equipment mounted on the exterior of the vehicle to avoid dislodging. Mounting units on the interior of the vehicle by a method other than permanent mount is discouraged as it may become detached under aggressive driving conditions such as sudden braking, collision, or swerving.

**PROPER INSTALLATION COMBINED WITH OPERATOR TRAINING IN THE PROPER USE OF EMERGENCY WARNING DEVICES IS ESSENTIAL TO ENSURE THE SAFETY OF EMERGENCY PERSONNEL AND THE PUBLIC.**



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

### **Important Points for Your Safety and Longevity of Your Light Bar**

- Installers are required to have a good understanding of automotive electronic systems and procedures for proper installation.
- Never stare directly into the LEDs as momentary blindness and/or eye damage may occur.
- Never take any lights through a car wash. Use only water to clean the outer body/lens of your equipment.
- Never use a pressure washer to clean any STL products. Inspect and test your product daily to insure it operates properly and is mounted correctly.
- Never cut wires or work on a unit while the unit is still connected to a power source.
- Never install this product or route any wires through or in the deployment area of the airbag. Doing so may cause serious personal injury as it will damage or reduce the effectiveness of the airbag by causing the unit to become a projectile. Reference the owner's manual for your vehicle to find the airbag deployment area. The User/Installer assumes all responsibility to determine proper mounting location, based on providing ultimate safety to all passengers in the vehicle.
- If the product requires you to drill holes, the installer must ensure that the drilling process does not damage any vehicle components or other vital parts. Check all sides of the mounting surface before beginning to drill. Make sure to deburr all drilled holes and remove any metal remnants or shards to avoid injury and wires from becoming spliced. Grommets are to be installed in all wire passage holes.
- In order for STL products to operate at optimum efficiency, a secure and good electrical connection to the battery's Ground Post must be made. The recommended procedure requires the unit's ground wire be connected directly to the NEGATIVE (-) battery post.
- Instruction manuals should be stored in a safe place for reference if you need to reinstall the unit or perform maintenance. They can also be found at the main site under the product listing at [www.SpeedTechLights.com](http://www.SpeedTechLights.com). If your product is no longer available on the website contact STL's Customer Service at 800-757-2581 for assistance.
- If your product requires the use of a control box or remote device to turn on and control your equipment make sure it is installed in a location that allows both the user and the vehicle to operate safely in any driving condition.
- Never activate or control your equipment in hazardous driving conditions.



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

- FAILURE TO FOLLOW THESE SAFETY PRECAUTIONS, WARNINGS, NOTICES, AND INSTRUCTIONS COULD RESULT IN DAMAGE TO THE PRODUCT OR VEHICLE THAT WILL VOID YOUR WARRANTY AND/OR CAUSE SERIOUS INJURY TO YOU AND YOUR PASSENGER.

**SUMMARY OF THE PRIME® 27" TIR:**

With super bright design that allows for 360° lighting with 56 powerful 3-Watt MaxGen™ LEDs, the STL Prime ® 27" TIR is perfect for your light bar needs. With features and options that give you the more for less the STL Prime ® Series cannot be beat GUARANTEED.

- Powered by 12V
- Weather-proof housing
- Double-layer aluminum alloy board fully enclosed in plastic
- 56 total 3-watt MaxGen™ LEDs
- 8 3-watt MaxGen™ LEDs in Alley Lights
- Eclipse® Technology TIR optics
- 15 available flash patterns
- Non-volatile memory recalls last flash pattern
- Lifespan of up to 100,000 hours
- Includes 13 feet of cable to switch box, 1.5 feet of power cable, and 8 feet of auxiliary cable
- Includes Magnet Brackets for Mounting
- Optional STL Grand Control Box w/ Alley Switch
- Optional Headache Rack Bracket
- Dimensions of Light bar: 22.75" L x 3.25" H x 12.87" D
- 9.1 AMP draw
- 7 day money back guarantee\*
- 5 year warranty\*

\* See Terms and Conditions for details

Wiring Diagram for power harness with three (3) colored leads: ALL CABLES SHOULD CONTACT TO +VDC

\* Indicates a main power cable

Yellow	Flash Pattern Selector
*Red	Positive
*Black	Negative

**How the STL Grand Control® Box With Alley Function Operates Your STL Light bar Left On/Off Switch (Plus Aux Switch)**

On Position: Turns on all the LED Modules in your light bar plus units attached to aux cables

Off Position: Turns off all the LED Modules in your light bar

\***Aux** (Red ((+) Positive) and Blue ((-) Negative) wires)

Rated for 10 AMPs



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

1st press: Power ON unit attached to aux cables

2nd press: Power OFF unit attached to aux cables

### **Flash Pattern Rocker Switch**

Cycles to the next flash pattern with each press. Non-Volatile memory recalls the last flash pattern selected.

### **Right On/Off/On Switch**

Top On Position: Turns on Alley Position Light Steady Burn

Off Position: Leaves Alley Position Light to Flash in Sequence with the Warning Pattern of the light bar

Lower On Position: Turns on Alley Position Light to Pulsing Flash

### **Unpacking your STL Product**

Unpack your unit to identify all parts including but not limited to: light bar, switch box, brackets, screws, bolts, wiring harness, fuses, etc.

Some parts may be in small bags.

Some products may be packaged inside boxes of other products.

Some parts such as Gutter Brackets, may be in the foam protection. Double check that no parts are left within the foam protection or left in the box.

### **Pre-Installation and Testing**

BENCH TEST all units prior to installation by connecting the Positive Cable (Red) and Negative Cable (Black) to a power source to ensure all the features and parts of the light bar are functional.

Test Check List:

- All LEDs and LED Modules fully functional
- Flash patterns
- Non-volatile memory
- No physical damage

If you have trouble call Customer Service at 800-757-2581 before proceeding.

### **Instructions for Mounting, Wiring and Programming**

IMPORTANT! To ensure proper installation installers are required to have a good understanding of automotive electronic, systems and procedures for proper installation. When you are drilling into the vehicle's surfaces, ensure that the area is free of any electrical wires, vehicle upholstery, fuel lines, etc. that could be damaged. All wiring passing through drilled holes should use



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

grommets and silicone sealant to prevent wire or moisture damage when passing through compartment walls.

**WARNING!** Larger wires and secure or tight connections will ensure longer service life for your product. It is highly recommended that soldered connections have heat shrink used to protect the connection. Special attention should be given to the location and method of splicing wires to make electrical connections to protect these splices from lost power or connection and corrosion. Insulation displacement connectors are not to be used. To reduce voltage drop, minimize the number of splices in the wires. The current carrying capacity of wires and fuses will be significantly reduced under high ambient temperature (e.g. under the hood). Use SXL type wire in the engine compartment where higher heat resistance is required according to SAE J-1128. All wires should be in accordance with the minimum wire size and other recommendations made by the manufacturer and be protected from hot surfaces and moving parts. Grommets, cable ties, looms, and other installation hardware should be used to anchor and protect all wiring. Fuses should be properly sized and located as close to the power take off points as possible to protect the wiring and device. To protect against short circuits, a fuse is included by STL for all products. Do NOT use a fuse with a higher amp rating than the initial fuse included. Do NOT use Circuit Breaks with STL Products. Ground terminations should only be made directly to the battery.

### **Mounting**

**WARNING!** Using a warning device with a magnet mount on the outside of a vehicle while it is in motion is at the sole risk and responsibility of the user. Seek a professional installer for assistance.

#### **Mounting: Magnet Mount**

- Clean the surface where the light bar will be mounted.
- Place the light bar on a flat surface of the vehicle and adjust the magnet feet to fit your vehicle according to the zones specified by the vehicle manufacture.
  - Light bars should be mounted a minimum of 12" - 34" from the radio antenna to avoid interference.
  - If do not know where to mount your bar, seek a professional installer for the installation of your light bar.

#### **Mounting: Permanent Mount**

**WARNING!** Do not drill through the roof support member which spans between the passenger and drivers side of the vehicle. If this applies to you, adjust the location where the bar will be mounted to avoid contact with this support member.

Option 1: Use Existing Brackets



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

- Remove the Magnet Brackets from the Light Bar by turning it upside down and unscrewing the bracket from the bar.
- Unscrew the Magnets from the brackets and use the existing holes to run a screw through the holes to hard mount the bar to your vehicle with the Magnet Brackets.
- Reattach the bracket back to the light bar and proceed with installation.

Option 2: Fabricate a Custom Bracket

**Warning!** Fabricating a Custom Bracket is at your own risk and must be durable enough to support your light bar and remain secure to the vehicle.

- Remove the Magnet Brackets from the Light Bar by turning it upside down and unscrewing the bracket from the bar.
- Measure the existing holes where the bracket was removed in the light bar to build a custom bracket.
- Attach the bracket to the light bar and proceed with installation.

#### **Mounting: Headache Rack Mount**

- Remove the Magnet Brackets from the Light Bar by turning it upside down and unscrewing the bracket from the bar.
- Use the existing holes and hardware to replace the Magnet Brackets with the Headache Rack Bracket.
- Reattach the Headache Rack Bracket to the light bar and proceed with installation.

#### **Wiring**

- Lower the headliner before drilling by 6" to 8" to protect it from damage caused by drilling the cable access hole.
- The Light bar's wire harness will require you to drill a hole for the cable access.
  - **WARNING!** Do not drill through the roof support member which spans between the passenger and drivers side of the vehicle. If this applies to you, adjust the location where the bar will be mounted to avoid contact with this support member.
- Remove all ridges or sharp edges of the hole with a round file. Make sure to de-burr the edges of the hole.
- You must use a grommet (USER SUPPLIED) into the cable access hole.
- Once the cables are fully pulled through, use RTV Silicone to weatherproof the hole.
- Route the full length of the cable down towards your switch panel through the base of the B-Pillar taking a 90 Degree turn to enter the B-pillar.

#### **Wiring: Connecting Wires to the Battery**

- **WARNING!** If you are supplying your own wiring that connects to the positive or negative terminal of the battery, fuse sizes must be sized according to STL's provided fuse to be considered fused properly to the battery in order to carry the load.





218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

- Route the power cables by opening the wiring shield and running the cables through it towards your vehicle's firewall.
- Follow the factory wiring harness through the firewall.
- If it is necessary to drill a hole in the firewall for the power cables, be sure no components will be damaged from drilling. As with all holes that are drilled, file the edges down smooth and insert a grommet to protect the cables.
- Route the cable along the factory wiring harness towards the battery.
- Wire your power cables (Red with In Line Fuse (STL Supplied) and Black cable) to your battery to power up your light bar.
- You will want to ensure your grounding cable is taken directly to the negative terminal of your battery to avoid any electrical feedback which may disrupt your light bar system.
- DO NOT allow the positive (Red wire) and negative (Black wire) to touch one another. This may cause injury to you and damage your equipment by causing a short in the unit that is not covered under the STL warranty.

#### **Wiring: Cigarette Lighter Plug**

- If you are using the Cigarette Lighter Plug follow the guidelines for Wiring to get the cables into the vehicle and plug the Cigarette Lighter Plug into your Cigarette outlet.

#### **Wiring: Connecting Wires to Control Box**

- This unit will feature a power harness with three (3) colored leads with a connector that plugs into the Cigarette Lighter Plug.
  - When not utilizing the Cigarette Lighter Plug reference the Wiring Diagram for power harness with three (3) colored leads
- Now that you have pulled the cable into the vehicle attach the connector back to your light bar's wire harness in the CORRECT positions using a pin pusher and plug it into your Cigarette Lighter Plug. If you do not know the correct position of each wire in the connector call customer service at 1-800-757-2581 before proceeding.
- If you are using your own switch box or the STL IntelliSiren, wire the cables accordingly into your control panel by referencing the wiring diagram and instruction manual of your control panel.

#### **Wiring: Connecting Extension Cables**

- This unit will feature a power harness with three (3) colored leads with a connector that plugs into the Cigarette Lighter Plug.
- If you have an extension cable with connectors, connect the corresponding ends to one another. Use the connector at the end of the cable to plug into your control box.
- If you have an extension cable with one connector, you will need to cut the connector off of the main cable harness coming out of the light bar. Save it as a spare part. You will solder, and heat shrink each wire within the cable harness to each wire in the extension





218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

cable harness. DO NOT cross connect wires. Use the connector at the end of the extension cable to plug into your control box.

- If you have an extension cable with no connectors, you will need to cut in the middle of the main cable harness coming out of the light bar. You will solder, and heat shrink each wire within the cable harness to each wire in the extension cable harness. DO NOT cross connect wires. Use the connector at the end of the main cable harness to plug into your control box.
  - DO NOT leave connectors, cables, solder points exposed to heat or moisture or debris.

### **Programming Flash Patterns**

- All STL LED products are equipped with a non-volatile memory which will recall the last flash pattern when the light bar is turned on.
- Set your flash pattern by pushing the Flash Pattern button on your Cigarette Lighter Plug to cycle through the various patterns until you find the appropriate pattern.
- If you are not using the Cigarette Lighter Plug you will follow the wiring diagram to identify the Flash Pattern wire to manually run through and select the desired flash pattern.

### **Maintenance**

While STL's light bars are very durable, there are some things you need to keep in mind and practice to preserve the longevity and function of your bar.

- Never take any STL Light bars through a car wash, such as a pressure washer, automatic car wash, brushes that will scratch your equipment or similar car washes or equipment where chemicals, high pressure water, and materials may scratch or damage your equipment.
- Use Water (H<sub>2</sub>O) with a soft cloth to clean your light bar and lenses.
- Yellowing of clear lenses may occur overtime. Lenses can be purchased by calling STL Customer Service at 800-757-2581.

### **Parts List**

End Caps  
Top Cover





218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

			<p>d. Make sure the pin is seated in the center of its pin position to ensure proper connection</p> <p>7. If not: continue reading:          1. Follow steps 1 - 4 to unplug a working module in the same manner.          2. Plug in the defective module into the working modules position.              a. If the LED module comes on. You need a new PCB              b. If the LED module does not come on. You need a new LED module</p>
No recall of flash pattern	<p>Is the units power cables run to the correct locations: Positive (red) and Negative (black), directly to the battery?</p> <p style="text-align: right;">No</p> <p style="text-align: right;">Yes</p>	<p>Improper Grounding.</p>	<p>If grounded incorrectly, an electrical feedback could be the culprit. Electrical feedback can cause the PCB not to recognize the command that it is being told to do. Move the ground to proper location and see if this fixes the issue.</p> <p>A New PCB may be required.</p>
Pressing buttons on the Switch Box but light bar doesn't respond at all or for specific function	<p>Does the STL Logo on the Grand Control Box light up when on?</p> <p style="text-align: right;">No</p>	<p>Improper Grounding.</p> <p>Broken Cigarette Plug</p>	<p>If grounded incorrectly, an electrical feedback could be the culprit. Electrical feedback can cause the PCB not to recognize the command that it is being told to do. Move the ground to proper location and see if this fixes the issue.</p> <p>Inspect to cigarette plug to make sure there is no damage or pulled wires from the plug. If so you will need to replace</p>



218 Trademark Dr • Buda • Texas • 78610

**Phone** 800.757.2581 • **Fax** 844.894.2652 • **Email** customerservice@speedtechlights.com

		<p>Broken Fuse</p> <p>Disconnected Connector</p> <p>Damaged Cable</p> <p>Yes TEST THE <b>POSSIBLE CAUSES</b> FOR "No"</p> <p>Wires in the wrong location</p>	<p>the Cigarette Plug</p> <p>If the cigarette plug is not damaged unscrew the cap of the cigarette plug to gain access to the fuse. Check to see if the fuse is broken. If do you will need to replace the Fuse.</p> <p>Check that the connector is fully recessed in the switch box. If you have an extension cable with connectors check that the connection has not disconnected.</p> <p>Check the full length of your wiring to make sure there are no spliced wired in the cable harness.</p> <p>TEST THE <b>POSSIBLE CAUSES</b> FOR "No"</p> <p>You may have a wire that is not in the correct position. If you are using an extension cable with connectors or no connector, make sure that the wires are corresponding correctly. In other words, simply make sure the colors are matching one another and that you do not have a Green connected to a Yellow. Green should be connected to Green.</p>
--	--	--	--

**Stay Safe and Continue Lighting the Way® with SpeedTech Lights®**

We know that Trust is Earned®! Thank you for giving STL the opportunity to earn your business and trust. Visit [www.SpeedTechLights.com](http://www.SpeedTechLights.com) for any additional information and services regarding STL Warranty, Return Policy, Videos, or any other Customer Service needs you deem necessary. Shop with Confidence® with SpeedTech Lights!

(c) 2016 SpeedTech Lights, Inc.

All rights reserved. No part of this Operations Manual and Instructions may be reproduced, distributed, transmitted, or otherwise shared in any form or by any means, including but not limited to photocopying, recording, electronic delivery, .pdf reproduction, or any other means of reproducing all or any part hereof without the express prior written consent of the SpeedTech Lights, Inc., except for non-commercial purposes as permitted by United States copyright law. Customers of SpeedTech Lights, Inc., may download and print this Operations Manual and Instructions for use with products sold to the customer by SpeedTech Lights, Inc. However, no part of the Operations Manual and Instructions may be otherwise or subsequently reproduced, downloaded, disseminated, published, or transferred, in any form or by any means, except with the prior written consent of SpeedTech Lights, Inc.