



# STL Boss 400

## SUMMARY:

With independent siren tones, the STL Boss is a 400-watt siren ideal for Police, Fire and EMS vehicles.

- Powered by 12V
- Clear sound frequency
- Multi-tone functionality which allows for independent siren tones to each speaker
- Amplifier output power of 400-watts
- Independent siren tones for easy selection
- Siren tones include: Wail, Yelp, Sting, Siren, Horn, Tool, Hi-lo
- Includes flat brackets for mounting amplifier
- Includes microphone with 2 feet of coiled cable which extends to 6 feet
- Includes 8.5 feet of cable to speakers and power
- Includes 10 feet of cable from amp to faceplate
- Speakers sold separately
- Amplifier Dimensions: 5" L x 2.5" H x 6.5" D
- Faceplate Dimensions: 5" L x 3" H x 1" D
- 7 day money back guarantee
- 1 year warranty

## INSTALLATION INSTRUCTIONS:

1. The Boss siren system comes with all cabling needed for installation
2. This system will include a telephone cable (one long and straight and one curly); these will connect with an adapter, also included.
3. It will also include (2) long red cables and (2) long black cables for power, and a gray connector with (2) orange, (2) green, (1) gray, and (1) yellow wires.
4. Connect the phone cable to the plug in on the power supply labeled "Signal Socket".
5. Then connect the Gray connector into the power supply to the right of the phone cable.
6. From the gray connector, you will wire the (2) orange wires to one speaker, and the (2) green wires to your second speaker. (The yellow and gray wires are for international use).
7. You will then connect the power cables, (2) red and (2) black, to the power supply. Each cable includes a connector at one end for you to screw to the power supply.
8. Connect the (2) black cables to the (2) negative slots on the power pack and the (2) red cables to the (2) positive slots.
9. Once you have connected all the wires correctly, wire up your (2) red power cables to the positive on your battery and your (2) black cables to the negative on your battery.
10. This will allow you to give power to the whole system.
11. Connect the other end of the phone cable to your face plate labeled "STL Boss" and connect your microphone to your face plate.
12. Turn the unit on and power its functions using the faceplate.
13. If you order a console bracket, insert the faceplate into the bracket and screw the faceplate to the bracket using the (4) corner holes.